

# Isaac

## Multi-Function Leak Tester



### **Flexibility and simplicity**

Zaxis' instruments are built to meet an ever-changing manufacturing environment. The products that Zaxis has conceived in the past 20 years, first as IDS of Salt Lake City, Utah and today as Zaxis Inc, Salt Lake City, are still in use today throughout the world.

### **Simply powerful**

The Isaac multi-tester is the newest product from Zaxis, designed to meet today's quality assurance demands.

The compact size of the Isaac enables it to be utilized in close proximity to test fixtures.

By reducing the test connection volume the test sensitivity increases and test times can be decreased. Additionally the internal volume of the Isaac is less than 1 cubic centimeter. The small internal volume combined with integrated sensors and a 24-bit analog to digital converter allow Zaxis to offer a leak tester with the highest sensitivity on the market. The Isaac is available for pressure/ vacuum decay, mass flow, burst and pressure cracking applications. The Isaac can be configured from one to four channels in a sequential or concurrent configuration depending upon applications

Zaxis Inc.  
79 West 4500 South #21 Salt Lake City, Utah, USA 801-264-1000  
[www.zaxisinc.com](http://www.zaxisinc.com)

# Isaac Specifications

Dimensions:..... 6W"x7H" x9D"

Precision..... 0.01%.

Pressure Range..... 0-15, 0-100 & 0-500 PSIG Positive Pressure. 0-15 PSI Vacuum.  
Other ranges available upon request

Media Compatibility..... Clean, dry, non-corrosive gasses compatible with Aluminum and 316 stainless steel.

Power ..... 115-230 VAC 50/60 Hz auto sensing, 60 watts

Display ..... 4" backlit graphical LCD Touch screen

Engineering Units..... PSI, inches of H<sub>2</sub>O, kPa, mbar, mmHg, sccm etc

Test types..... Standard: Pressure decay, occlusion  
Optional: Vacuum Decay, Mass Flow, crack pressure, Burst & more

Stored Programs..... 100

Interface..... RS232, TCP/IP (Ethernet)

Auxiliary Outputs..... 24Vdc PLC interface

Time..... 0.1-999.9 seconds

Resolution..... Pressure: .00001 PSI  
mass flow: range dependant typically .01 SCCM

Storage..... -20 to 70°C

Test port fitting..... 1/8 NPT female bulkhead

Controls..... Graphical touch screen, 22.5 mm NEMA 13 Lighted pushbuttons and indicators

